CUSTOM PRINTED GLAZED PORCELAIN TILE

PRODUCT CLASSIFICATION: GROUP BIb (Conforms to UNI EN 14411 GROUP B1b APPENDIX H)

WATER ABSORPTION CONFORMS TO ISO 10545-3 0.5%-3%

FROST RESISTANCE: CONFORMS TO ISO 10545-12

THERMAL SHOCK RESISTANCE: CONFORMS TO ISO 10545-9

FLEXURAL STRENGTH: ISO 10545-4 N/mm2 30±50

CHEMICAL RESISTANCE: RESISTANCE TO ACIDS AND ALKALIS, WITH THE EXCEPTION OF HYDROFLUORIC ACID RESISTANCE, CONFORMS TO ISO 10545-13

LINEAR THERMAL EXPANSION: ISO 10545-8 ≤ 7 MK

PEI RESISTANCE TO ABRASION: ISO 10545-7 **PEI 4** Suitable for Moderate to Heavy Traffic, Residential and Commercial – not recommended for sloped, wet surfaces.

DIMENSIONAL FEATURES: WARPAGE CONFORMS TO ISO 10545-2 ± 0.5%

CRAZING RESISTANCE: CONFORMS TO ISO 10545-11

CUSTOM TILES, LLC
custom-tiles.com
+1 434-660-7170